



## Deep / Preparation Cleaning Of Porous Building Material

1. External Natural Stone and concrete paving also suitable for garden walls and timber decking = **Stontex All In One Outdoor Cleaner 5L**, coverage rate depends on how dirty the material is but average 5L = 30sqm. Do Not Spray, mix in bucket 1 to 1 and apply with a deck brush agitate well and solution will foam up like shampoo allow to dwell for up to 30mins then power wash / hose the area with water.
2. External Natural Stone, Brick, Roof Tiles, Render and Wooden cladded walls = **Stontex Green To Clean 5L**, coverage rate depends on how dirty the material is but average 5L = 80sqm. Spray the diluted 1 to 5 mix, onto the stained surface and allow to dwell overnight then power wash / hose the area with water.
3. Internal Natural Stone, ceramic and porcelain internal floor tiles = **Stontex Heavy Duty Grime Remover 1L**, coverage rate depends on how dirty the material is but average 1L = 50sqm, dilute 1 to 10 and apply by agitating surface with a nylon brush allow to dwell for 15mins and wash thoroughly with clean water.

## Protection Of Porous Building Material

1. Natural Stone paving / tiles with natural look finish = **Stontex Rapid Dry Stone Sealer 1L & 5L**, coverage rate 8sqm to 12sqm depending on porosity of the material, normally 1 coat treatment but additional coat may be required for added protection.
2. Natural Stone paving / tiles with wet look finish = **Stontex Colour Intensifier 1L & 5L** coverage rate 8sqm to 12sqm depending on porosity of the material, normally 1 coat treatment but additional coat may be required to uniform the colour.
3. Natural Stone, Brick, Render, cladded walls also Roof Tiles to achieve a natural look finish = **Stontex Façade Pro500 25L**, coverage rate 4sqm to 8sqm depending on porosity of the material, normally 1 coat treatment but additional coat may be required for added protection.
4. Mono Block / Concrete Block paving driveways natural look finish (additional coats will give a wet look) = **Stontex Paver Plus 5L & 25L**, coverage rate 3sqm to 6sqm depending on size of the blocks, normally 1 coat treatment but additional coats may be required to enhance the colour. Consolidates the kiln dried sand in the joints and seals the face of the paver for stain protection.



## Ongoing Maintenance Of Porous Building Material

- 1 External Natural Stone and concrete paving also suitable for garden walls and timber decking = **Stontex Green to Clean 5L**, coverage rate depends on how dirty the material is but average 5L = 100sqm. Spray directly onto the algae/ lichen stained surface, mix in a 25L knapsack sprayer 1x 5L green to clean and fill rest of container with water this is a full-strength mix. Pick a dry day as needs to be dry at least four hours after application, then simply spray and walk away within a few days up to two weeks all organic stains will be gone and active enzymes will continue to work for up to 9 months. No power washing or scrubbing of any kind cleaner activated by UV new innovative technology.
- 2 External Natural Stone, Brick, Roof Tiles, Render and Wooden cladded walls = **Stontex Green To Clean 5L**, coverage rate depends on how dirty the material is but average 5L = 100sqm. Spray directly onto the algae/ lichen stained surface, mix in a 25L knapsack sprayer 1x 5L green to clean and fill rest of container with water this is a full-strength mix. Pick a dry day as needs to be dry at least four hours after application, then simply spray and walk away within a few days up to two weeks all organic stains will be gone and active enzymes will continue to work for up to 9 months. No power washing or scrubbing of any kind cleaner activated by UV new innovative technology
- 3 Internal Natural Stone, ceramic and porcelain floor tiles = **Stontex Multi Clean 1L**, coverage rate average 1L = 800sqm, dilute 1 to 50 and apply by mop and bucket however a steam mop would be much better that way you are not moving the dirty water all around the floor. Our **Stontex Multi Clean 1L** is also a disinfectant kills e-coli, MRSA and other common bacteria and has a unique streak free formula for polished floor tiles.